



GWI GROUP LIMITED

44-60 Zhongshan Road, Qingdao, China

Tel : 0086-532-82021369,82021969 Fax:0086-532-82021697



Polyester monofilament mesh

Fabric Number	Mesh Count	Thread Diameter	Mesh Opening	Open Surface	Fabric Thickness	Weight	Theoretic deposit Ink Volume	Tension
NO./cm	mesh/inch	um	um	%	um	g/m2	cm3/m2	N/cm
10T	25	250	750	56	500	165	280	66
14T	36	200	514	52	400	150	208	61
16T	40	200	425	46	400	160	184	58
18S	45	150	405	53	300	120	159	57
18T	45	180	375	46	350	150	161	60
20S	50	100	400	64	200	33	128	50
20T	50	150	350	49	300	115	147	53
20T	50	180	320	41	350	138	143	56
24S	60	80	337	61	134	65	82	40
24S	60	100	316	57	167	81	95	49
24T	60	120	297	51	204	97	104	52
24T	60	150	267	41	255	120	105	56
28S	70	80	277	60	134	76	80	46
28T	70	100	257	52	170	95	88	49
30T	76	120	213	41	200	103	82	55
32S	80	80	232	55	135	53	74	40
32T	80	100	212	45	165	75	73	54
32T	80	120	192	38	200	90	73	60
34T	86	100	194	44	172	78	76	56
36S	90	80	193	46	134	60	59	48
36T	90	100	173	41	166	75	68	56
39S	99	55	177	56	88	30	55	30
39T	99	64	168	52	135	40	70	48
39T	99	71	161	48	114	44	55	60
40T	100	80	166	44	130	60	59	37
43T	110	80	149	41	130	64	53	35
47S	120	55	152	51	88	34	48	33
47T	120	64	143	48	110	48	53	35
47T	120	71	136	44	125	59	55	47
51S	130	55	140	51	100	45	51	30
51T	130	71	125	41	140	63	57	43
53S	135	55	133	50	86	40	42	34
53T	135	64	125	44	100	51	39	40
53T	135	71	110	35	116	62	40	47
56S	142	55	126	48	111	42	53	35
56T	142	64	114	41	115	49	47	41
59S	150	55	114	46	105	45	48	31
59T	150	64	105	39	120	61	46	40
61T	155	64	90	31	101	58	30	41
64S	163	55	98	38	98	48	36	33
64T	163	64	85	30	115	61	34	42
68S	173	55	85	34	85	48	28	36
68T	173	64	78	28	105	65	30	40
72S	183	48	90	36	78	39	33	34
72T	183	55	85	30	90	51	27	38
77S	195	48	77	35	80	42	28	30
77T	195	55	67	27	88	55	24	33
80T	200	48	72	33	74	56	25	34
90T	230	48	56	25	78	50	19	32
100T	255	40	58	33	63	37	21	32
110HD	280	40	48	27	64	40	17	34
120T	305	34	45	30	55	35	16	34
120HD	305	40	37	20	63	44	13	33
130T	330	34	40	27	55	37	15	33
140T	355	34	31	20	53	39	10	33
150S	380	31	32	23	49	32	11	31
150T	380	34	23	13	55	42	6.5	33
165S	420	27	29	22	44	29	10.5	24
165T	420	31	25	17	46	36	10	27
180T	460	27	22	16	44	31	6.8	24
200(TW)	500	31	14	8	43	26	7	26